

PF200 SEDIMENT FILTRATION

• Up to 200 GPM • 75 PSI



FEATURES

- Dual bag and cartridge filtration
- Two (2) bag filters for high solids holding capacity
- One (1) multiple cartridge filter for high solids removal efficiency
- Replaceable filtration cartridges from 100 to .5 micron nominal rating
- Manifold valving for ease of use
- No moving parts
- Skid mounted

TECHNICAL

- Bag filters are used with cartridge filters in series to provide efficient filtration
- Units fitted with bleed valves and pressure gauges
- Initial pressure drop is less than 5 psi at 200 gpm
- System can stand alone for sediment removal or be used in combination with media vessels.
- Multiple cartridge filters provide large surface area for longer service life.

MATERIAL SPECIFICATIONS

- Chambers constructed out of 304 stainless steel
- Piping construction: 3" Stainless Steel
- 3" Cam inlet and outlet
- Each bag filter chamber holds one (1) 7" x 30" double-stitched filter bag
- Cartridge chamber holds twelve (12) 40" long double open-ended cartridges with 2-1/2" OD and 1" ID
- Maximum operating pressure 75 psig



4101 Union Avenue
Bakersfield, CA 93305
877 324 9634 • 661 324 9634
661 322 4206 Fax
www.clearcreeksystems.com